

Model	Voltage (V - Hz)	Speed	Power (W)	Airflow (m³/h)	Static Pressure (Pa)	Noise (dB)	Exchange Efficiency - Cooling	Exchange Efficiency - Heating	Enthalpy Exchange Rate - Cooling	Enthalpy Exchange Rate - Heating	N.W (Kg)
KCQR - 1000	220 - 50	H/L	600/500	1000/800	245/210	48/46	62/64	58/71	61/65	60/66	66.5
KCQR - 1500	220 - 50	H/L	1100/900	1500/1200	265/230	52/50	63/68	60/72	62/68	60/70	67
KCQR - 2000	220 - 50	H/L	1400/1200	2000/1700	270/245	55/53	64/69	61/73	63/68	60/71	83
KCQR - 2500	220 - 50	/	1600/1400	500/2200	285/255	56/53	64/69	63/76	63/68	60/72	85
KCQR - 3000	220/380 - 50	/	1900	3000	275	57	69	79	68	68	106.5
KCQR - 4000	220/380 - 50	/	2200	4000	305	58	69	79	68	71	107.5
KCQR - 5000	380 - 50	/	3000	5000	320	60	69	79	68	71	164
KCQR - 6000	380 - 50	/	3300	6000	345	62	69	73	68	71	195
KCQR - 8000	380 - 50	/	4400	8000	370	65	70	76	69	72	284